



S X N THREAD
DN ØP
BOLT CIRCLE

SIZE	A	B	C	D	E	F	G	H	J	L	M	N	P	S	Q
2	3.04	5.99	4.69	1.63	4.00	1.09	0.56	0.43	0.406	3.00	3.25	.625-11	4.75	4	1.41
3	3.54	7.24	4.87	1.75	4.00	1.09	0.56	0.43	0.406	3.00	3.25	.625-11	6.00	4	2.62
4	4.63	8.74	6.00	2.00	4.00	1.09	0.62	0.43	0.406	3.00	3.25	.625-11	7.50	8	3.62
6	6.37	11	6.50	2.14	4.00	1.09	1.00	0.43	0.406	3.00	3.25	.750-10	9.50	8	5.68

VALVE DIMENSIONS (IMPERIAL - INCHES)

ITEM NO.	NAME	QTY	REMARKS
1	BDDY	1	
2	DISC	1	
3	LINER	1	
4	STEM, UPPER	1	
5	STEM, LOWER	1	
6	BEARING	4	
7	PIN, RETENTION	2	
8	TAG	1	

NOTE:

1. 'Q' DIMENSION IS THE MINIMUM ALLOWABLE PIPE OR FLANGE INSIDE DIAMETER AT THE CENTERED BODY FACE TO PROTECT THE DISC SEALING EDGE AGAINST DAMAGE WHEN OPENING THE VALVE.

Grinnell

MODEL 8000 316SS LUG
2", 3", 4", 6"

101-802-8

NO. 1	DRAWN JVB	DATE 3/1/03	CHECK JS
			DATE 3/1/03

SHEET 1 OF 2